

USA Price Schedule

North American Models - 120 Volts, 60Hz.

	MSRP/MAP
<p>PurePower™ 3000</p> <ul style="list-style-type: none"> • 3000VA/2100 watts continuous load, 3200 watts short duration, 6300 watts peak • 25 amps RMS, 37 amps short duration, 75 amps peak • 6 Hubbell 5-15/20R outlets, 2 Hubbell L5-20R locking outlets • 30 amp input power cord with L5-30P plug and wall receptacle included. (Must have 30 amp circuit and #10 AWG wiring from electrical panel) • World's most powerful audio AC regenerator, designed for high power systems 	<p>\$4,995.00</p> 
<p>PurePower™ 2000</p> <ul style="list-style-type: none"> • 2000VA/1400 watts continuous load, 2100 watts short duration, 4200 watts peak • 16.6 amps RMS, 25 amps short duration, 50 amps peak • 10 Hubbell 5-15R outlets • 20 amp input locking power cord included • World's 2nd most powerful audio AC regenerator, designed for high power amps 	<p>\$3,695.00</p> 
<p>PurePower™ 1050</p> <ul style="list-style-type: none"> • 1500VA/1050 watts continuous load, 1500 watts short duration, 3150 watts peak • 12.5 amps RMS, 18 amps short duration, 36 amps peak • 8 Hubbell NEMA 5-15 outlets • Ideal for high end audio and mid power 7.1 ch home theater 	<p>\$2,495.00</p> 
<p>PurePower™ PowerPack</p> <ul style="list-style-type: none"> • Additional battery reserve for PurePower™ units • Increases battery operating time up to 2 hours • Can be daisy chained for up to 8 hours • Specify PowerPack 36V for PurePower 1050 • Specify PowerPack 72V for purePower 2000 • Specify PowerPack 96V for purePower 3000 	<p></p> <p>\$1495.00 \$1595.00 \$1695.00</p>
<p>PurePower™ Accessories</p> <ul style="list-style-type: none"> • Stabilizing foot allows vertical placement. Specify 1050 or 2000/3000 model • Replacement 36V sealed high rate discharge battery kit for 1050 • Replacement 72V sealed high rate discharge battery kit for 2000 • Replacement 96V sealed high rate discharge battery kit for 3000 	<p>\$30.00 \$200.00 \$400.00 \$500.00</p>

All APS PurePower™ models

- Available in silver or black anodized finish
- Include rack mount handles, input line cord
- 12-15 minutes internal battery operation at 1/2 load
- Surge protection for: RJ11 (phone), RJ45 (network), and F-type coax (2), cULus approved

- Serial and USB data ports support control systems such as Crestron® and AMX®
- Optional vertical mounting feet available

Terms: Prepaid by VISA/Mastercard/Amex or wire transfer.
No CODs.

Shipping: FOB our warehouse.

For product info, please contact:

PUREPOWER PARTNERS LLC.
148 Northumberland St., Unit 4
Ayr, ON
Canada N0B 1E0
Phone (519) 624-9735
Fax (888) 336-4293
Sales@PurePowerAPS.com